



## 28' Multi-Temp Refrigerated Trailer

<b>Exterior Dimensions</b>	Length 28' Height: 13' 6" Width: 102"
<b>Interior Dimensions</b>	Width 96 5" Height 103.5"
<b>5<sup>th</sup> Wheel Pin Location</b>	24"
<b>Landing Gear Location</b>	93" centerline kingpin to centerline landing gear

### Refrigeration Unit

<b>Fuel Tank</b>	50 Gallon Aluminum anti-siphon
<b>Air Return Bulkhead</b>	F/G Vortex w/Pallet Stops
<b>Location of Remove Evap</b>	Remote Evaporator is located at C/L 179"
<b>Upper Coupler Height</b>	47" (+/- ½")
<b>Anti Nose Dive Leg</b>	OEM Standard mounted on C/S
<b>Crossmembers</b>	OEM Standard for heavy duty application steel on 12" C/L with two additional at rear for 8" C/L placement.

### Suspension

<b>Suspension Type</b>	Spring ride – Binkley DuraSystem, 3 leaf heavy duty springs
<b>ABS</b>	OEM 2s/1M
<b>Auto Tire Inflation</b>	Meritor or Hendrickson PSI

### Rear Door Options

<b>Rear Door Type</b>	RUD – 2 1/8" Whiting Cold Saver w/stainless steel hardware and dual seals Swing – OEM Standard smooth white aluminum w/vent & anti theft bars
<b>Grab Handle</b>	If RUD selected, 36" x 1" round stainless grab handle If Swing selected, 36" round stainless grab handle mounted on R/S door

## Interior

<b>E-Trac</b>	Two row recessed E-Trac mounted at 30" and 60" C/L
<b>Foam Package</b>	3" Wall, 3.5" Ceiling, 3" Floor, 4" Nose
<b>Interior Light Placement*</b>	(3) 10-diode LED lights with electronic timer switch If Center divide then (2 pair) evenly spaced front to back
<b>Liner/Scuff/Floor</b>	Puncture resistant liner on all surfaces with heavy duty aluminum scuff on heavy duty dry freight or duct anti slip floor

## Side Doors

<b>1<sup>st</sup> Side Door Location</b>	Curbside 12" from leading edge of trailer to leading edge of door. Minimum 72" x 40" opening with stirrup step.
<b>2<sup>nd</sup> Side Door</b>	None

## Liftgate/Ramp

<b>Liftgate Rating</b>	All steel platform 84" wide by 86" long + 16" rated at 5500 lbs capacity
<b>Retention Ramp</b>	16" aluminum
<b>Pump</b>	Dual Pump and Motor
<b>Power</b>	Dual Pole charging system with both dual pole and single pole fixture Phillips # 280275-06
<b>Ramp</b>	16' Gladiator aluminum ramp with spring assist mounted in fully enclosed carrier at rear of trailer (non-liftgate units)

NOTE: The foregoing are general. Actual specifications may vary by individual trailers.

\*All lighting locations are approximate; manufacturer specs may vary.