



### 53' Single-Temp Refrigerated Trailer

|  |  |
|--|--|
| <b>Exterior Dimensions</b>               | Length 53'<br>Height: 13' 6"<br>Width: 102"          |
| <b>Interior Dimensions</b>               | Width 96 5"<br>Height 104"                           |
| <b>5<sup>th</sup> Wheel Pin Location</b> | 36"  |
| <b>Landing Gear Location</b>             | 104.5" centerline kingpin to centerline landing gear |

#### Refrigeration Unit

|                                |  |
|--------------------------------|--|
| <b>Fuel Tank</b>               | 50 Gallon Aluminum anti-siphon   |
| <b>Air Return Bulkhead</b>     | F/G Vortex w/Pallet Stops  |
| <b>Location of Remove Evap</b> | N/A  |
| <b>Upper Coupler Height</b>    | 47" (+/- ½")   |
| <b>Anti Nose Dive Leg</b>      | None   |
| <b>Crossmembers</b>            | OEM Standard for heavy duty application steel on 12" C/L with two additional at rear for 8" C/L placement. |

#### Suspension

|                            |  |
|----------------------------|--|
| <b>Suspension Type</b>     | Air ride – Hendrickson HKANT 40, with Surelok option |
| <b>ABS</b>                 | OEM 2s/1M  |
| <b>Auto Tire Inflation</b> | Meritor or Hendrickson PSI                           |

#### Rear Door Options

|                       |  |
|-----------------------|--|
| <b>Rear Door Type</b> | RUD – 2 1/8" Whiting Cold Saver w/stainless steel hardware and dual seals<br>Swing – OEM Standard smooth white aluminum w/vent & anti theft bars |
| <b>Grab Handle</b>    | If RUD selected, 36" x 1" round stainless grab handle<br>If Swing selected, 36" round stainless grab handle mounted on R/S door                  |

## Interior

|                                  |   |
|----------------------------------|---|
| <b>E-Trac</b>                    | None, support for e-trac will be placed at 30" and 60" for future installation  |
| <b>Foam Package</b>              | 2" Wall, 3" Ceiling, 3" Floor, 4" Nose  |
| <b>Interior Light Placement*</b> | None  |
| <b>Liner/Scuff/Floor</b>         | Puncture resistant liner on all surfaces with heavy duty aluminum scuff on heavy duty dry freight or duct anti slip floor |

## Side Doors

|  |      |
|--|------|
| <b>1<sup>st</sup> Side Door Location</b> | None |
| <b>2<sup>nd</sup> Side Door</b>          | None |

## Liftgate/Ramp

|                        |  |
|------------------------|--|
| <b>Liftgate Rating</b> | All steel platform 84" wide by 86" long + 16" rated at 5500 lbs capacity   |
| <b>Retention Ramp</b>  | 16" aluminum   |
| <b>Pump</b>            | Dual Pump and Motor  |
| <b>Power</b>           | Dual Pole charging system with both dual pole and single pole fixture Phillips # 280275-06                               |
| <b>Ramp</b>            | 16' Gladiator aluminum ramp with spring assist mounted in fully enclosed carrier at rear of trailer (non-liftgate units) |

NOTE: The foregoing are general. Actual specifications may vary by individual trailers.

\*All lighting locations are approximate; manufacturer specs may vary.